Site Inspection Checklist				
te Address:	Month:			
spector Name:	Project Start Date: Project End Date:			
one:	Project End Date.			
USE THIS CHECKLIST FOR REGULAR SITE INSPECTION, AT MINIMUM ONCE PER WEEK AND BEFORE HEAVY PRECIPITATION OR OTHER WEATHER-RELATED DISTURBANCES				
Item and/or Location to Check	Inspection Dates			
ain Events		1		
a rain event greater than 20mm in 12 hours expected? If yes verify all controls are in excellent working order lead of the rain.				
ersonnel and Vehicles				
ave all personnel on site been made aware of the requirements for erosion and sediment control and the insequences involved if there is a breach?				
ave construction vehicles exposed soils, removed vegetation, or compacted root systems? If so communicate the sue to drivers and remediate the area.				
as it been communicated to heavy machinery to bypass the proposed infiltration area (as noted on ESC plan) to duce risk of compaction during construction where possible?				
verland Flow				
"clean water" diverted around the disturbed area?	П	П	П	П
e concentrated flows of runoff being directed into a sediment pond?	П		П	П
ediment Pond				
e the embankments of the pond and the areas that lie downstream stabilized?	П			П
the pond system in good working condition?				
ccumulated sediment is removed before pond reaches 50% capacity heck Dams				
			Τ –	
re the straw bale dams checked regularly (including immediately after each rainfall) and paired/replaced if integrity is compromised?				
e the straw bale check dams keyed into the ditch and staked with two stakes angled towards the adjacent bale?				
loose straw wedged between bales to create a continuous barrier?				
the excavated soil backfilled and compacted against the bale on the upslope side?				
It Fence				
the geotextile still buried in the soil on the upslope side of the stakes?		П		П
the fence pulled tight so it won't sag when water builds up behind it?				
e the ends brought upslope compared to the rest of the fence to prevent runoff from going around the ends?				
ave all the gaps and tears in the fence been eliminated?	П	П	П	П
the excavated soil backfilled and compacted against the fence on the upslope side?	П	П	П	П
as the built up sediment reached 1/3 of the height of the sediment fence? yes, remove sediment and make necessary fence repairs.				
isturbed Areas and Stock Piles				
the upslope run-off diversion of sandbags, fibre or geofabric that is in good working order (i.e. continuous barrier				
operly installed)? the stock pile located upslope of an appropriate sediment barrier (wall of sandbags, fibre or geotextile) that is in bod working order (i.e. continuous barrier properly installed)?				
re stockpiles unlikely to be used for over 14 days or , if a heavy rain is imminent, been temporarily abilized (wind and waterproof coverings held down by weights) in their entireties?				
cabilization				
as seed and mulch been applied at the proper rate?				
as seed or mulch blown away? If so, replace.				
rainfall has been inadequate, have seeded areas been watered?	П	П	П	П
there evidence of erosion on previously stabilized areas? If so investigate using other stabilization methods.				
oall operational storm sewer inlets have inlet protection in good working order (i.e. continuous barrier properly stalled)?				
ollution Control		·	'	1
re fuel tanks and drums of toxic and hazardous materials stored within a diked area or trailer and away from any atercourse, ditch or storm drain?				
otes		1	1	